

NATIONAL DECLARATION OF PERFORMANCE
nr 04/2024

1. Name and trade name of the construction product:

GAMRAT decking board 140x25 SLIM

2. Designation of construction product type:

GAMRAT decking board 140x25 SLIM

3. Intended use(s):

GAMRAT decking board 140x25 SLIM is intended for outdoor flooring with light and low traffic (terraces, verandas, balconies – individual users).

4. Manufacturer's name and registration Office address and place of production:

Gamrat WPC Sp. z o.o.
Ul. Mickiewicza 108
38-200 Jasło

5. Authorized representative's name and register office address, if any:

not applicable

6. The national system used to assess and verify the constancy of performance:

System 4

7. National technical specification:

7a. Polish Standard for the product:

PN-EN 15534

Name of the accredited certification body, accreditation number and national certificate number or the name of the accredited laboratory/ laboratories and accreditation number:

not applicable

7b. National Technical Assessment:

not applicable

Technical assessment unit/ National technical assessment unit:

not applicable

Name of the accredited certification body, accreditation number and certificate number:

not applicable

8. Declared performance characteristics:

Essential characteristic of the construction product for the intended use or uses	Declared performance characteristics	Notes
Dimensional deviations, mm: - length - width - overall thickness	(-0 / +10) ± 1,0 ± 1,0	
Straightness of the edges, mm/m	≤ 0,7	
Transverse curvature, mm	≤ 0,7	
Bending properties of boards (clear spacing of supports 450 mm) - destructive force, N - deflection under load 500N, mm	average value ≥ 3300 single value ≥ 3000 average value ≤ 2,0 single values ≤ 2,5	
Swelling after 28 days of immersion in water at temp. (+20 ± 2)°C, % - in the length direction - in the width direction - in the direction of thickness	average value ≤ 0,4 single value ≤ 0,6 average value ≤ 0,8 single value ≤ 1,2 average value ≤ 4,0 single value ≤ 5,0	
Absorbability after 28 days of immersion in water at temp. (+20 ± 2)°C, %:	average value ≤ 6,0 single value ≤ 6,0	
Slip resistance of the floor, for dry and wet Surface, PTV:	≥ 55	

GAMRAT SLIM board is made of non-flammable materials – flammability group B.

9. The performance of the product specified above is in accordance with all the declared performance characteristics listed in section 8. This declaration of performance is issued in accordance with the Act of April 16, 2004 on Construction Products, under the sole responsibility of the manufacturer.

Signed for and behalf of the manufacturer by:

Marek Sepioł – Head Director of Gamrat WPC

Jasło, 04.07.2024

Prezes Zarządu

 Marek Sepioł